



MARBLE TEXTURE

EXF – 1000

DESCRIPTION	SYSTEM RECOMMENDATION																															
<p>A premium quality exterior/interior vinyl/acrylic emulsion based Marble Texture finish. This product has been formulated to provide excellent exterior durability, hiding of imperfections and tough flexible finish. An alternative to Granite, which exhibits a natural finish. Posh and luxurious decorative coating that provides a shield through all seasons.</p>	<p>Concrete Block:</p> <table border="0"> <tr> <td>Acrylic Primer Sealer</td> <td>1 Coat</td> <td>Respective DFT per coat (S) <u>or</u> (W)</td> </tr> <tr> <td>Marble Texture</td> <td>1 Coat</td> <td>600 – 1000 Microns DFT</td> </tr> <tr> <td>Optional Topcoats</td> <td>1 Coat</td> <td>As Recommended</td> </tr> </table>	Acrylic Primer Sealer	1 Coat	Respective DFT per coat (S) <u>or</u> (W)	Marble Texture	1 Coat	600 – 1000 Microns DFT	Optional Topcoats	1 Coat	As Recommended																						
Acrylic Primer Sealer	1 Coat	Respective DFT per coat (S) <u>or</u> (W)																														
Marble Texture	1 Coat	600 – 1000 Microns DFT																														
Optional Topcoats	1 Coat	As Recommended																														
<p>RECOMMENDED USES</p>	<p>Asbestos Siding, Gypsum Board:</p>																															
<p>For use over prepared substrate such as drywall, plaster, vinyl sidings, plywood, concrete block and other masonry and metal surfaces in architectural application.</p>	<table border="0"> <tr> <td>Masonry Conditioner</td> <td>1 Coat</td> <td>25 Microns DFT</td> </tr> <tr> <td>Marble Texture</td> <td>1 Coat</td> <td>600 – 1000 Microns DFT</td> </tr> <tr> <td>Optional Topcoats</td> <td>1 Coat</td> <td>As Recommended</td> </tr> </table>	Masonry Conditioner	1 Coat	25 Microns DFT	Marble Texture	1 Coat	600 – 1000 Microns DFT	Optional Topcoats	1 Coat	As Recommended																						
Masonry Conditioner	1 Coat	25 Microns DFT																														
Marble Texture	1 Coat	600 – 1000 Microns DFT																														
Optional Topcoats	1 Coat	As Recommended																														
<p>CHARACTERISTICS</p>	<p>Wood/Fiber Board:</p>																															
<table border="0"> <tr> <td>Color:</td> <td>Wide range of colors available</td> </tr> <tr> <td>Finish:</td> <td>Granite look with sheen</td> </tr> <tr> <td>Volume Solid:</td> <td>67.0% ± 2%</td> </tr> <tr> <td>Specific Gravity:</td> <td>1.82 KG / ltr</td> </tr> <tr> <td>Recommended DFT:</td> <td>600 – 1000 Microns</td> </tr> <tr> <td>Spreading Rate@DFT:</td> <td>0.4 – 0.6 m² / KG</td> </tr> <tr> <td>Flash Point:</td> <td>94 °C</td> </tr> <tr> <td>Drying Schedule:</td> <td>Dry to Touch: 1 - 1½ Hour</td> </tr> <tr> <td>@ 25 °C/R.H.50</td> <td>Hard Dry: 24 Hours</td> </tr> <tr> <td>Shelf Life:</td> <td>18 months, unopened at 25 °C</td> </tr> <tr> <td>Reducer/Clean Up:</td> <td>Water</td> </tr> </table>	Color:	Wide range of colors available	Finish:	Granite look with sheen	Volume Solid:	67.0% ± 2%	Specific Gravity:	1.82 KG / ltr	Recommended DFT:	600 – 1000 Microns	Spreading Rate@DFT:	0.4 – 0.6 m ² / KG	Flash Point:	94 °C	Drying Schedule:	Dry to Touch: 1 - 1½ Hour	@ 25 °C/R.H.50	Hard Dry: 24 Hours	Shelf Life:	18 months, unopened at 25 °C	Reducer/Clean Up:	Water	<table border="0"> <tr> <td>Wall & Wood Primer</td> <td>1 Coat</td> <td>50 Microns DFT</td> </tr> <tr> <td>Marble Texture</td> <td>1 Coat</td> <td>600 – 1000 Microns DFT</td> </tr> <tr> <td>Optional Topcoats</td> <td>1 Coat</td> <td>As Recommended</td> </tr> </table> <p>Optional Topcoats:</p> <ul style="list-style-type: none"> • Hi-Build Aliphatic Polyurethane (Clear) • Sheracryl Acrylic Enamel (Clear) 	Wall & Wood Primer	1 Coat	50 Microns DFT	Marble Texture	1 Coat	600 – 1000 Microns DFT	Optional Topcoats	1 Coat	As Recommended
Color:	Wide range of colors available																															
Finish:	Granite look with sheen																															
Volume Solid:	67.0% ± 2%																															
Specific Gravity:	1.82 KG / ltr																															
Recommended DFT:	600 – 1000 Microns																															
Spreading Rate@DFT:	0.4 – 0.6 m ² / KG																															
Flash Point:	94 °C																															
Drying Schedule:	Dry to Touch: 1 - 1½ Hour																															
@ 25 °C/R.H.50	Hard Dry: 24 Hours																															
Shelf Life:	18 months, unopened at 25 °C																															
Reducer/Clean Up:	Water																															
Wall & Wood Primer	1 Coat	50 Microns DFT																														
Marble Texture	1 Coat	600 – 1000 Microns DFT																														
Optional Topcoats	1 Coat	As Recommended																														
<p>ADVANTAGES</p>	<p>*For further information on recommended products please refer to Sherwin Williams Saudi Arabia Painting & Coatings System Guide.</p>																															
<ul style="list-style-type: none"> • Resistant to UV light • Reflects incoming sun rays up to 92% • Lowers the cost of energy • Anti-Carbonation properties and Salt Resistant • Regulates humidity & heat 	<p>**For further information on surface preparation methods and application procedures please refer to Sherwin Williams Saudi Arabia Surface Preparation bulletin.</p>																															
<p>APPLICATION PROCEDURES</p>	<p>SPECIAL TIPS</p>																															
<p>Surface Preparation: Surface must be dry, clean and in sound condition. Remove oil, dust, dirt, millscale or other foreign substance to ensure good adhesion. Minimum surface preparation methods to be followed for concrete, plaster, cement, etc. is to allow curing for 30 days. Mildew must be removed prior to painting by washing with a solution of 1 quart household bleach and 3 quarts warm water.</p> <p>Application Methods:</p> <table border="0"> <tr> <td>Texture Hopper Gun Spray:</td> <td>Reduce up to 12% with water</td> </tr> <tr> <td>Trowel (Small Areas < 1 Ft²):</td> <td>Reduction not recommended</td> </tr> </table>	Texture Hopper Gun Spray:	Reduce up to 12% with water	Trowel (Small Areas < 1 Ft²):	Reduction not recommended	<p>Excessive reduction of material can affect the film build, appearance, and adhesion. Any further specific technical information can be obtained from SWSA if you email ask@sherwinwilliams.ae</p> <p>SAFETY PRECAUTIONS</p> <p>Spray under well-ventilated conditions. Do not breathe or inhale mist. When spraying, wear air mask. Avoid skin contact. Spillage on skin should immediately be removed with suitable cleanser, soap and water. Eyes should be flushed with water and medical attention sought immediately.</p>																											
Texture Hopper Gun Spray:	Reduce up to 12% with water																															
Trowel (Small Areas < 1 Ft²):	Reduction not recommended																															