



SHER-SHIELD TEXTURE FINE AGGREGATE

EPF – Series

DESCRIPTION	SYSTEM RECOMMENDATION																																	
<p>A superior quality exterior/interior 100% acrylic emulsion, fast drying based fine texture finish. This pleasing texture, which results, has the ability to hide concrete/masonry imperfections and irregularities. The unusual adhesion and quality of the particles in Sher-Shield grants the product with ability of minimizing defects on poured cement, aggregate blocks, and joints.</p>	<p>Concrete Blocks, Cement Plastered Walls:</p> <table border="0"> <tr> <td>Latex Wall Primer or</td> <td>1 Coat</td> <td>25 Microns DFT</td> </tr> <tr> <td>Acrylic Primer Sealer (S) or (W)</td> <td>1 Coat</td> <td>25 Microns DFT</td> </tr> <tr> <td>Sher-Shield Texture Fine Aggregate</td> <td>2 Coats</td> <td>75 Microns DFT per coat</td> </tr> <tr> <td>Optional Topcoat</td> <td>1 - 2 Coats</td> <td>As Recommended</td> </tr> </table>	Latex Wall Primer or	1 Coat	25 Microns DFT	Acrylic Primer Sealer (S) or (W)	1 Coat	25 Microns DFT	Sher-Shield Texture Fine Aggregate	2 Coats	75 Microns DFT per coat	Optional Topcoat	1 - 2 Coats	As Recommended																					
Latex Wall Primer or	1 Coat	25 Microns DFT																																
Acrylic Primer Sealer (S) or (W)	1 Coat	25 Microns DFT																																
Sher-Shield Texture Fine Aggregate	2 Coats	75 Microns DFT per coat																																
Optional Topcoat	1 - 2 Coats	As Recommended																																
<p>RECOMMENDED USES</p>	<p>Asbestos Siding, Gypsum Board:</p>																																	
<p>For use over prepared substrate such as drywall, plaster, vinyl sidings, plywood, concrete block and other masonry and metal surfaces in architectural application.</p>	<table border="0"> <tr> <td>Masonry Conditioner</td> <td>1 Coat</td> <td>25 Microns DFT</td> </tr> <tr> <td>Sher-Shield Texture Fine Aggregate</td> <td>2 Coats</td> <td>75 Microns DFT per coat</td> </tr> <tr> <td>Optional Topcoat</td> <td>1 - 2 Coats</td> <td>As Recommended</td> </tr> </table>	Masonry Conditioner	1 Coat	25 Microns DFT	Sher-Shield Texture Fine Aggregate	2 Coats	75 Microns DFT per coat	Optional Topcoat	1 - 2 Coats	As Recommended																								
Masonry Conditioner	1 Coat	25 Microns DFT																																
Sher-Shield Texture Fine Aggregate	2 Coats	75 Microns DFT per coat																																
Optional Topcoat	1 - 2 Coats	As Recommended																																
<p>CHARACTERISTICS</p>	<p>Wood / Fiber Board:</p>																																	
<table border="0"> <tr> <td>Color:</td> <td>Wide range of colors available</td> </tr> <tr> <td>Finish:</td> <td>Texture Finish</td> </tr> <tr> <td>Volume Solid:</td> <td>64.0% ± 1%</td> </tr> <tr> <td>Specific Gravity:</td> <td>1.65 KG / ltr</td> </tr> <tr> <td>Recommended DFT:</td> <td>150 Microns</td> </tr> <tr> <td>Spreading Rate@DFT:</td> <td>1 m² / KG</td> </tr> <tr> <td>Flash Point:</td> <td>94 °C</td> </tr> <tr> <td>Drying Schedule:</td> <td></td> </tr> <tr> <td>@ 25 °C/R.H.50</td> <td>Dry to Touch: 1- 1½ Hours</td> </tr> <tr> <td></td> <td>Hard Dry: 24 Hours</td> </tr> <tr> <td>Shelf Life:</td> <td>18 months, unopened at 25 °C</td> </tr> <tr> <td>Reducer/Clean Up:</td> <td>Water</td> </tr> </table>	Color:	Wide range of colors available	Finish:	Texture Finish	Volume Solid:	64.0% ± 1%	Specific Gravity:	1.65 KG / ltr	Recommended DFT:	150 Microns	Spreading Rate@DFT:	1 m ² / KG	Flash Point:	94 °C	Drying Schedule:		@ 25 °C/R.H.50	Dry to Touch: 1- 1½ Hours		Hard Dry: 24 Hours	Shelf Life:	18 months, unopened at 25 °C	Reducer/Clean Up:	Water	<table border="0"> <tr> <td>Wall & Wood Primer</td> <td>1 Coat</td> <td>50 Microns DFT</td> </tr> <tr> <td>Sher-Shield Texture Fine Aggregate</td> <td>2 Coats</td> <td>75 Microns DFT per coat</td> </tr> <tr> <td>Optional Topcoat</td> <td>1 - 2 Coats</td> <td>As Recommended</td> </tr> </table> <p>Optional Topcoats:</p> <ul style="list-style-type: none"> • Exterior Plastic Emulsion • Sherwin Fine Emulsion • Flat Tone Latex Finish • Weatherclad (Gloss, Semigloss, Flat) • Latex Satin Finish • Sheracryl (Gloss, Semigloss, Flat, Clear) • Hi-Build Aliphatic Polyurethane (Clear, Enamel) <p>*For further information on recommended products please refer to Sherwin Williams Saudi Arabia Painting & Coatings System Guide.</p> <p>**For further information on surface preparation methods and application procedures please refer to Sherwin Williams Saudi Arabia Surface Preparation bulletin.</p>	Wall & Wood Primer	1 Coat	50 Microns DFT	Sher-Shield Texture Fine Aggregate	2 Coats	75 Microns DFT per coat	Optional Topcoat	1 - 2 Coats	As Recommended
Color:	Wide range of colors available																																	
Finish:	Texture Finish																																	
Volume Solid:	64.0% ± 1%																																	
Specific Gravity:	1.65 KG / ltr																																	
Recommended DFT:	150 Microns																																	
Spreading Rate@DFT:	1 m ² / KG																																	
Flash Point:	94 °C																																	
Drying Schedule:																																		
@ 25 °C/R.H.50	Dry to Touch: 1- 1½ Hours																																	
	Hard Dry: 24 Hours																																	
Shelf Life:	18 months, unopened at 25 °C																																	
Reducer/Clean Up:	Water																																	
Wall & Wood Primer	1 Coat	50 Microns DFT																																
Sher-Shield Texture Fine Aggregate	2 Coats	75 Microns DFT per coat																																
Optional Topcoat	1 - 2 Coats	As Recommended																																
<p>APPLICATION PROCEDURES</p>	<p>SPECIAL TIPS</p>																																	
<p>Surface Preparation: Surface must be dry, clean and in sound condition. Remove oil, dust, dirt, millscale or other foreign substance to ensure good adhesion. Minimum surface preparation methods to be followed for concrete, plaster, cement, etc. is to allow curing for 30 days. Mildew must be removed prior to painting by washing with a solution of 1 quart household bleach and 3 quarts warm water.</p> <p>Application Methods:</p> <table border="0"> <tr> <td>Conventional Spray:</td> <td>Reduce up to 12% with water</td> </tr> <tr> <td>Airless Spray:</td> <td>Reduce up to 12% with water</td> </tr> <tr> <td>Brush/Roller:</td> <td>Reduction not recommended</td> </tr> </table>	Conventional Spray:	Reduce up to 12% with water	Airless Spray:	Reduce up to 12% with water	Brush/Roller:	Reduction not recommended	<p>Excessive reduction of material can affect the film build, appearance, and adhesion. Any further specific technical information can be obtained from SWSA if you email ask@sherwinwilliams.ae</p> <p>SAFETY PRECAUTIONS</p> <p>Spray under well-ventilated conditions. Do not breathe or inhale mist. When spraying, wear air mask. Avoid skin contact. Spillage on skin should immediately be removed with suitable cleanser, soap and water. Eyes should be flushed with water and medical attention sought immediately.</p>																											
Conventional Spray:	Reduce up to 12% with water																																	
Airless Spray:	Reduce up to 12% with water																																	
Brush/Roller:	Reduction not recommended																																	