



# MAR-O-TEX

EFF – Series

DESCRIPTION	SYSTEM RECOMMENDATION
<p>A premium quality exterior/interior vinyl/acrylic emulsion based texture finish. This product has been formulated to provide excellent interior/exterior durability, hiding of imperfections, tough flexible finish, and has special chemicals that incorporate sound damping properties.</p>	<p><b>Iron and Steel:</b>            Antirust Metal Primer 1 Coat 30 Microns DFT            Grey            Mar-O-Tex 2 Coats 250 Microns DFT per coat</p>
RECOMMENDED USES	<p><b>Asbestos Siding, Gypsum Board:</b>            Masonry Conditioner 1 Coat 25 Microns DFT            Mar-O-Tex 2 Coats 250 Microns DFT per coat</p>
<p>For use over prepared substrate such as drywall, plaster, vinyl sidings, plywood, concrete block and other masonry and metal surfaces in architectural application.</p>	<p><b>Concrete Block:</b>            Heavy Duty Block Filler 1 Coat 250 Microns DFT            Mar-O-Tex 2 Coats 250 Microns DFT per coat</p>
CHARACTERISTICS	<p><b>Wood/Fiber Board:</b>            Wall &amp; Wood Primer 1 Coat 50 Microns DFT            Mar-O-Tex 2 Coats 250 Microns DFT per coat</p>
<p><b>Color:</b> Wide range of colors available  <b>Finish:</b> Texture Finish  <b>Volume Solid:</b> 42.0% ± 1%  <b>Specific Gravity:</b> 1.2 KG / ltr  <b>Recommended DFT:</b> 250 Microns  <b>Spreading Rate@DFT:</b> 1 m<sup>2</sup> / KG  <b>Flash Point:</b> 94 °C  <b>Drying Schedule:</b> <b>Dry to Touch:</b> 1 – 1 ½ Hours  <b>@ 25 °C/R.H.50</b> <b>Hard Dry:</b> 24 Hours</p> <p><b>Shelf Life:</b> 18 months, unopened at 25 °C  <b>Reducer/Clean Up:</b> Water</p>	<p><b>Previously Painted Surfaces:</b> Surfaces should be free from all foreign material. Old paint films must be brush blasted or scuff sanded prior to coating. Unknown old paint surface should be tested for lifting or peeling. If it does, clean to sound substrate and treat as new surface.</p> <p><b>Concrete &amp; Cement Surface:</b> All surfaces must be fully cured. Roughen the surface by sand blasting, shot blasting, mechanical scarification or suitable chemical means. Patch holes and cracks with an appropriate filler. The surface should be made free from moisture if any before application of the paint. Test the surface for moisture-free.</p> <p>*For further information on recommended products please refer to Sherwin Williams Saudi Arabia Painting &amp; Coatings System Guide.</p> <p>**For further information on surface preparation methods and application procedures please refer to Sherwin Williams Saudi Arabia Surface Preparation bulletin.</p>
APPLICATION PROCEDURES	SPECIAL TIPS
<p><b>Surface Preparation:</b> Surface must be dry, clean and in sound condition. Remove oil, dust, millscale or other foreign substance to ensure good adhesion. Minimum surface preparation methods to be followed for concrete, plaster, cement, etc. Is to allow curing for 30 days. Mildew must be removed prior to painting by washing with a solution of 1 quart household bleach and 3 quarts warm water.</p> <p><b>Application Methods:</b>            Spray application with hopper gun. No further reduction required.</p>	<p>Excessive reduction of material can affect the film build, appearance, and adhesion. Any further specific technical information can be obtained from SWSA if you email <a href="mailto:ask@sherwinwilliams.ae">ask@sherwinwilliams.ae</a></p> <p><b>SAFETY PRECAUTIONS</b></p> <p>Spray under well-ventilated conditions. Do not breathe or inhale mist. When spraying, wear air mask. Avoid skin contact. Spillage on skin should immediately be removed with suitable cleanser, soap and water. Eyes should be flushed with water and medical attention sought immediately.</p>