



SHER-RIVER 3MM

EXF – 3000

DESCRIPTION	SYSTEM RECOMMENDATION																						
<p>A Superior quality exterior vinyl/acrylic emulsion based 3mm river texture finish. This product has been formulated to provide excellent exterior durability, hiding of imperfections, esthetic looks and tough flexible finish.</p>	<p>Concrete Blocks/Cement Plastered Walls/Masonry Surfaces:</p> <table border="0"> <tr> <td>Recommended Primers</td> <td>1 Coat</td> <td>As Recommended</td> </tr> <tr> <td>Sher-River 3MM</td> <td>1 Coat</td> <td>800 Microns DFT</td> </tr> <tr> <td>Optional Topcoat</td> <td>1 Coat</td> <td>As Recommended</td> </tr> </table>	Recommended Primers	1 Coat	As Recommended	Sher-River 3MM	1 Coat	800 Microns DFT	Optional Topcoat	1 Coat	As Recommended													
Recommended Primers	1 Coat	As Recommended																					
Sher-River 3MM	1 Coat	800 Microns DFT																					
Optional Topcoat	1 Coat	As Recommended																					
RECOMMENDED USES																							
<p>For use over prepared substrate such as drywall, plaster, vinyl sidings, plywood, concrete block and other masonry and metal surfaces in architectural application.</p>	<p>Old/Chalky Powdered Cement Plastered Surfaces:</p> <table border="0"> <tr> <td>Acrylic Primer Sealer</td> <td>1 Coat</td> <td>25 Microns DFT</td> </tr> <tr> <td>Sher-River 3MM</td> <td>1 Coat</td> <td>800 Microns DFT</td> </tr> <tr> <td>Optional Topcoat</td> <td>1 Coat</td> <td>As Recommended</td> </tr> </table>	Acrylic Primer Sealer	1 Coat	25 Microns DFT	Sher-River 3MM	1 Coat	800 Microns DFT	Optional Topcoat	1 Coat	As Recommended													
Acrylic Primer Sealer	1 Coat	25 Microns DFT																					
Sher-River 3MM	1 Coat	800 Microns DFT																					
Optional Topcoat	1 Coat	As Recommended																					
CHARACTERISTICS																							
<table border="0"> <tr> <td>Color:</td> <td>Wide range of colors available</td> </tr> <tr> <td>Finish:</td> <td>Texture Finish</td> </tr> <tr> <td>Volume Solid:</td> <td>60.0% ± 1%</td> </tr> <tr> <td>Specific Gravity:</td> <td>1.93 KG / ltr</td> </tr> <tr> <td>Recommended DFT:</td> <td>800 – 1500 Microns</td> </tr> <tr> <td>Spreading Rate@DFT:</td> <td>0.4 - 0.75 m² / KG</td> </tr> <tr> <td>Flash Point:</td> <td>94 °C</td> </tr> <tr> <td>Drying Schedule:</td> <td>Dry to Touch: 5 – 6 Hours</td> </tr> <tr> <td>@ 25 °C/R.H.50</td> <td>Hard Dry: 24 Hours</td> </tr> <tr> <td>Shelf Life:</td> <td>18 months, unopened at 25 °C</td> </tr> <tr> <td>Reducer/Clean Up:</td> <td>Water</td> </tr> </table>	Color:	Wide range of colors available	Finish:	Texture Finish	Volume Solid:	60.0% ± 1%	Specific Gravity:	1.93 KG / ltr	Recommended DFT:	800 – 1500 Microns	Spreading Rate@DFT:	0.4 - 0.75 m ² / KG	Flash Point:	94 °C	Drying Schedule:	Dry to Touch: 5 – 6 Hours	@ 25 °C/R.H.50	Hard Dry: 24 Hours	Shelf Life:	18 months, unopened at 25 °C	Reducer/Clean Up:	Water	<p>Primers Recommended:</p> <ul style="list-style-type: none"> • Acrylic Primer Sealer (S) <u>or</u> (W) • Latex Wall Primer • Wall & Wood Primer <p>Topcoats Recommended:</p> <ul style="list-style-type: none"> • Sheracryl Acrylic Enamel (Clear) • Hi-Build Aliphatic Polyurethane (Clear)
Color:	Wide range of colors available																						
Finish:	Texture Finish																						
Volume Solid:	60.0% ± 1%																						
Specific Gravity:	1.93 KG / ltr																						
Recommended DFT:	800 – 1500 Microns																						
Spreading Rate@DFT:	0.4 - 0.75 m ² / KG																						
Flash Point:	94 °C																						
Drying Schedule:	Dry to Touch: 5 – 6 Hours																						
@ 25 °C/R.H.50	Hard Dry: 24 Hours																						
Shelf Life:	18 months, unopened at 25 °C																						
Reducer/Clean Up:	Water																						
ADVANTAGES																							
<ul style="list-style-type: none"> • Resistant to UV light • Reflects incoming sun rays up to 92% • Lowers the cost of energy • Anti-Carbonation properties and Salt Resistant • Regulates humidity & heat 	<p>*For further information on recommended products please refer to Sherwin Williams Saudi Arabia Painting & Coatings System Guide.</p> <p>**For further information on surface preparation methods and application procedures please refer to Sherwin Williams Saudi Arabia Surface Preparation bulletin.</p>																						
APPLICATION PROCEDURES	SPECIAL TIPS																						
<p>Surface Preparation: Surface must be dry, clean and in sound condition. Remove oil, dust, millscale or other foreign substance to ensure good adhesion. Minimum surface preparation methods to be followed for concrete, plaster, cement, etc. Is to allow curing for 30 days. Mildew must be removed prior to painting by washing with a solution of 1 quart household bleach and 3 quarts warm water.</p> <p>Application Methods:</p> <p>(1) Use Steel Trowel for application. The product can be reduced up to 5% with water.</p> <p>(2) Wood or plastic Trowel for leveling / structuring. When an area of 1 to 3 square meters is applied by steel trowel surface must be immediately leveled with plastic or wooden Trowel.</p>	<p>Excessive reduction of material can affect the film build, appearance, and adhesion. Any further specific technical information can be obtained from SWSA if you email ask@sherwinwilliams.ae</p> <p>SAFETY PRECAUTIONS</p> <p>Spray under well-ventilated conditions. Do not breathe or inhale mist. When spraying, wear air mask. Avoid skin contact. Spillage on skin should immediately be removed with suitable cleanser, soap and water. Eyes should be flushed with water and medical attention sought immediately.</p>																						