



MARBLE MARMITEX FINISH

EXF – 2000

DESCRIPTION	SYSTEM RECOMMENDATION																								
<p>Marble Marmitex Finish is a special effect traditional product. Designed to suit today's trends without losing quality and creating artistic attractive decorative effects.</p>	<p>Concrete & Plastered Walls:</p> <table border="0"> <tr> <td>Latex Wall Primer</td> <td>1 Coat</td> <td>30 Microns DFT</td> </tr> <tr> <td>Marble Marmitex Finish</td> <td>2 Coats</td> <td>500 Microns DFT per Coat</td> </tr> </table>	Latex Wall Primer	1 Coat	30 Microns DFT	Marble Marmitex Finish	2 Coats	500 Microns DFT per Coat																		
Latex Wall Primer	1 Coat	30 Microns DFT																							
Marble Marmitex Finish	2 Coats	500 Microns DFT per Coat																							
RECOMMENDED USES	<p>Gypsum Board:</p> <table border="0"> <tr> <td>Latex Wall Primer</td> <td>1 Coat</td> <td>30 Microns DFT</td> </tr> <tr> <td>Marble Marmitex Finish</td> <td>2 Coats</td> <td>500 Microns DFT per Coat</td> </tr> </table>	Latex Wall Primer	1 Coat	30 Microns DFT	Marble Marmitex Finish	2 Coats	500 Microns DFT per Coat																		
Latex Wall Primer	1 Coat	30 Microns DFT																							
Marble Marmitex Finish	2 Coats	500 Microns DFT per Coat																							
<p>Marble Marmitex Finish is specially formulated for use on walls, ceilings and other curved surfaces, leaving a joint free finish. It is highly recommended for prestigious projects such as Luxury Villas, Hotels, Restaurants, Palaces, Malls, Mosques, Museums, and Art Galleries. The lightweight surface (maximum thickness 3 mm) enables architects to make considerable cost savings on basic construction costs. Each finish is individually designed to suit the tastes and requirements of the designers.</p>	<p>Wood/Fiber Board:</p> <table border="0"> <tr> <td>Wall & Wood Primer</td> <td>1 Coat</td> <td>50 Microns DFT</td> </tr> <tr> <td>Marble Marmitex Finish</td> <td>2 Coats</td> <td>500 Microns DFT per Coat</td> </tr> <tr> <td>Kemlac Lacquer (W)</td> <td>1 Coat</td> <td>25 Microns DFT</td> </tr> </table>	Wall & Wood Primer	1 Coat	50 Microns DFT	Marble Marmitex Finish	2 Coats	500 Microns DFT per Coat	Kemlac Lacquer (W)	1 Coat	25 Microns DFT															
Wall & Wood Primer	1 Coat	50 Microns DFT																							
Marble Marmitex Finish	2 Coats	500 Microns DFT per Coat																							
Kemlac Lacquer (W)	1 Coat	25 Microns DFT																							
CHARACTERISTICS	<ul style="list-style-type: none"> All surfaces must be treated with a key coat to ensure good adhesion of the product to the background surface. Finishes must be mixed with water and then applied in a number of thin layers to build a thickness of 2-3 mm. When dry, color washing may be necessary for some of the finishes. After curing, surface could be oiled and/or waxed according to the architects specification. For use in bathrooms or kitchens the surface can be treated with water proofing sealer. Adjacent surfaces cannot be plastered simultaneously. Work areas should be staggered to allow adjoining surfaces to dry. 																								
<table border="0"> <tr> <td>Color:</td> <td>Wide range of colors available</td> </tr> <tr> <td>Finish:</td> <td>Antique</td> </tr> <tr> <td>Volume Solid:</td> <td>62% ± 2%</td> </tr> <tr> <td>Specific Gravity:</td> <td>1.77 KG / ltr</td> </tr> <tr> <td>Recommended DFT:</td> <td>500 Microns</td> </tr> <tr> <td>Spreading Rate@DFT:</td> <td>1.24 m² / ltr or 4.69 m² / US gallon</td> </tr> <tr> <td>Flash Point:</td> <td>94 °C</td> </tr> <tr> <td>Drying Schedule:</td> <td>Dry to Touch: 4 Hours</td> </tr> <tr> <td>@ 25 °C/R.H.50</td> <td>To Handle: 24 Hours</td> </tr> <tr> <td></td> <td>To Recoat: 12 Hours</td> </tr> <tr> <td>Shelf Life:</td> <td>12 months, unopened at 25 °C</td> </tr> <tr> <td>Reducer/Clean Up:</td> <td>Water</td> </tr> </table>	Color:	Wide range of colors available	Finish:	Antique	Volume Solid:	62% ± 2%	Specific Gravity:	1.77 KG / ltr	Recommended DFT:	500 Microns	Spreading Rate@DFT:	1.24 m ² / ltr or 4.69 m ² / US gallon	Flash Point:	94 °C	Drying Schedule:	Dry to Touch: 4 Hours	@ 25 °C/R.H.50	To Handle: 24 Hours		To Recoat: 12 Hours	Shelf Life:	12 months, unopened at 25 °C	Reducer/Clean Up:	Water	<p>*For further information on recommended products please refer to Sherwin Williams Saudi Arabia Painting & Coatings System Guide.</p> <p>**For further information on surface preparation methods and application procedures please refer to Sherwin Williams Saudi Arabia Surface Preparation bulletin.</p>
Color:	Wide range of colors available																								
Finish:	Antique																								
Volume Solid:	62% ± 2%																								
Specific Gravity:	1.77 KG / ltr																								
Recommended DFT:	500 Microns																								
Spreading Rate@DFT:	1.24 m ² / ltr or 4.69 m ² / US gallon																								
Flash Point:	94 °C																								
Drying Schedule:	Dry to Touch: 4 Hours																								
@ 25 °C/R.H.50	To Handle: 24 Hours																								
	To Recoat: 12 Hours																								
Shelf Life:	12 months, unopened at 25 °C																								
Reducer/Clean Up:	Water																								
APPLICATION PROCEDURES	SPECIAL TIPS																								
<p>Surface Preparation: Surface must be dry, clean and in sound condition. Remove oil, dust, dirt, millscale or other foreign substance to ensure good adhesion. To achieve the required finish we strongly recommend that only decorative effect trained craftsman applies this product.</p> <p>Application Methods:</p> <p>Trowel, Steel Spatula.</p>	<p>Excessive reduction of material can affect the film build, appearance, and adhesion. Any further specific technical information can be obtained from SWSA if you email ask@sherwinwilliams.ae</p> <hr/> <p>SAFETY PRECAUTIONS</p> <p>Apply under well-ventilated conditions. Do not breathe or inhale mist. When spraying, wear air mask. Avoid skin contact. Spillage on skin should immediately be removed with suitable cleanser, soap and water. Eyes should be flushed with water and medical attention sought immediately.</p>																								