



# ACRYLIC LATEX PUTTY INTERIOR

EYF – W804

DESCRIPTION	SYSTEM RECOMMENDATION												
<p>Acrylic Latex Putty Interior is a ready mixed filler based on a terpolymer acrylic latex binder and pigments carefully selected to impart toughness and maximum filling.</p>	<p><b>Concrete &amp; Cinder Block/Masonry:</b></p> <table border="0"> <tr> <td>Recommended Primer</td> <td>1 Coat</td> <td>Respective DFT</td> </tr> <tr> <td>Acrylic Latex Putty Interior</td> <td>1 Coat</td> <td>250 Microns DFT</td> </tr> <tr> <td>Recommended Primer</td> <td>1 Coat</td> <td>Respective DFT</td> </tr> <tr> <td>Recommended Topcoats</td> <td>2 Coats</td> <td>Respective DFT per coat</td> </tr> </table>	Recommended Primer	1 Coat	Respective DFT	Acrylic Latex Putty Interior	1 Coat	250 Microns DFT	Recommended Primer	1 Coat	Respective DFT	Recommended Topcoats	2 Coats	Respective DFT per coat
Recommended Primer	1 Coat	Respective DFT											
Acrylic Latex Putty Interior	1 Coat	250 Microns DFT											
Recommended Primer	1 Coat	Respective DFT											
Recommended Topcoats	2 Coats	Respective DFT per coat											
RECOMMENDED USES	<p><b>Previously Painted Masonry:</b></p> <table border="0"> <tr> <td>Masonry Conditioner</td> <td>1 Coat</td> <td>25 Microns DFT</td> </tr> <tr> <td>Acrylic Latex Putty Interior</td> <td>1 Coat</td> <td>250 Microns DFT</td> </tr> <tr> <td>Recommended Topcoats</td> <td>1 Coat</td> <td>Respective DFT per coat</td> </tr> </table>	Masonry Conditioner	1 Coat	25 Microns DFT	Acrylic Latex Putty Interior	1 Coat	250 Microns DFT	Recommended Topcoats	1 Coat	Respective DFT per coat			
Masonry Conditioner	1 Coat	25 Microns DFT											
Acrylic Latex Putty Interior	1 Coat	250 Microns DFT											
Recommended Topcoats	1 Coat	Respective DFT per coat											
CHARACTERISTICS	<p><b>Primers Recommended:</b></p> <ul style="list-style-type: none"> <li>Acrylic Primer Sealer (S) <u>or</u> (W)</li> <li>Latex Wall Primer</li> <li>Wall &amp; Wood Primer</li> </ul> <p><b>Topcoats Recommended:</b></p> <ul style="list-style-type: none"> <li>Exterior Plastic Emulsion</li> <li>Sherwin Fine Emulsion</li> <li>Flat Tone Latex Finish</li> <li>Weatherclad (Gloss, Semigloss, Flat)</li> <li>Latex Satin Finish</li> <li>Alkyd Enamels (Flat, Eggshell, Semigloss, Hi-Gloss)</li> <li>Sheracryl Acrylic Enamel (Gloss, Semigloss, Flat, Clear)</li> </ul> <p>*For further information on recommended products please refer to Sherwin Williams Saudi Arabia Painting &amp; Coatings System Guide.</p> <p>**For further information on surface preparation methods and application procedures please refer to Sherwin Williams Saudi Arabia Surface Preparation bulletin.</p>												
<p><b>Color:</b> White</p> <p><b>Finish:</b> Flat</p> <p><b>Volume Solid:</b> 55.0% ± 2%</p> <p><b>Specific Gravity:</b> 1.74 KGs / ltr</p> <p><b>Recommended DFT:</b> 200 - 250 Microns</p> <p><b>Spreading Rate@DFT:</b> 02.75 m<sup>2</sup>/ltr or 10.40 m<sup>2</sup> / US gallon</p> <p><b>Flash Point:</b> 94 °C</p> <p><b>Drying Schedule: @ 25 °C/R.H.50</b></p> <table border="0"> <tr> <td><b>Dry to Touch:</b></td> <td>1 Hour</td> </tr> <tr> <td><b>To Handle:</b></td> <td>6 Hours</td> </tr> <tr> <td><b>To Recoat:</b></td> <td>18 Hours</td> </tr> </table> <p><b>Shelf Life:</b> 18 months, unopened at 25 °C</p> <p><b>Reducer/Clean Up:</b> Water</p>	<b>Dry to Touch:</b>	1 Hour	<b>To Handle:</b>	6 Hours	<b>To Recoat:</b>	18 Hours	<p><b>Primerers Recommended:</b></p>						
<b>Dry to Touch:</b>	1 Hour												
<b>To Handle:</b>	6 Hours												
<b>To Recoat:</b>	18 Hours												
APPLICATION PROCEDURES	SPECIAL TIPS												
<p><b>Surface Preparation:</b> Surface must be dry, clean and in sound condition. Remove oil, dust, dirt, millscale or other foreign substance to ensure good adhesion. Concrete, brick and other similar surfaces should be cured for about six weeks before painting. Mildew must be removed prior to painting by washing with a solution of 1quart household bleach and 3 quarts warm water.</p> <p><b>Application Methods:</b> Steel Edged Spatula / Putty knife</p>	<p>Any further specific technical information can be obtained from SWSA if you email <a href="mailto:ask@sherwinwilliams.ae">ask@sherwinwilliams.ae</a></p> <p><b>SAFETY PRECAUTIONS</b></p> <p>Spray under well-ventilated conditions. Do not breathe or inhale mist. When spraying, wear air mask. Avoid skin contact. Spillage on skin should immediately be removed with suitable cleanser, soap and water. Eyes should be flushed with water and medical attention sought immediately.</p>												