



INDUSTRIAL LACQUER PUTTY

LYF W816 White
 LYF A801 Gray
 LYF R815 Red Oxide

DESCRIPTION	SYSTEM RECOMMENDATION																																			
<p>A general purpose nitrocellulose type lacquer putty for quality wood furniture and metal finishing. It fills open wood grains, scratches and delivers a smooth surface for finishing.</p>	<p>Iron and Steel:</p> <table border="0"> <tr> <td>Lacquer Primer Surfacer</td> <td>1 Coat</td> <td>25 Microns DFT</td> </tr> <tr> <td>Industrial Lacquer Putty</td> <td>1 Coat</td> <td>150 Microns DFT</td> </tr> <tr> <td>Industrial Lacquer</td> <td>2 Coats</td> <td>25 Microns DFT per coat</td> </tr> </table>	Lacquer Primer Surfacer	1 Coat	25 Microns DFT	Industrial Lacquer Putty	1 Coat	150 Microns DFT	Industrial Lacquer	2 Coats	25 Microns DFT per coat																										
Lacquer Primer Surfacer	1 Coat	25 Microns DFT																																		
Industrial Lacquer Putty	1 Coat	150 Microns DFT																																		
Industrial Lacquer	2 Coats	25 Microns DFT per coat																																		
RECOMMENDED USES	ALUMINUM AND GALVANIZED METAL:																																			
<p>For use over prepared wood and metal surface in the cabinet, toys, and the automotive industry.</p>	<table border="0"> <tr> <td>Wash Primer Green</td> <td>1 Coat</td> <td>07 Microns DFT</td> </tr> <tr> <td>Industrial Lacquer Putty</td> <td>1 Coat</td> <td>150 Microns DFT</td> </tr> <tr> <td>Industrial Lacquer</td> <td>2 Coats</td> <td>25 Micron DFT per coat</td> </tr> </table>	Wash Primer Green	1 Coat	07 Microns DFT	Industrial Lacquer Putty	1 Coat	150 Microns DFT	Industrial Lacquer	2 Coats	25 Micron DFT per coat																										
Wash Primer Green	1 Coat	07 Microns DFT																																		
Industrial Lacquer Putty	1 Coat	150 Microns DFT																																		
Industrial Lacquer	2 Coats	25 Micron DFT per coat																																		
CHARACTERISTICS	NATURAL WOOD/FIBERBOARD/PLYWOOD (PIGMENTED FINISH):																																			
<table border="0"> <tr> <td>Color:</td> <td>Above colors</td> </tr> <tr> <td>Finish:</td> <td>Flat</td> </tr> <tr> <td>Volume Solid:</td> <td>45% ± 2%</td> </tr> <tr> <td>Specific Gravity:</td> <td>1.40 KGs / ltr</td> </tr> <tr> <td>Recommended DFT:</td> <td>100 – 150 Microns</td> </tr> <tr> <td>Spreading Rate@DFT:</td> <td>4.50 m² / ltr or 17 m² / US gallon</td> </tr> <tr> <td>Flash Point:</td> <td>4 °C</td> </tr> <tr> <td>Drying Schedule:</td> <td></td> </tr> <tr> <td>@ 25 °C/R.H.50</td> <td>Dry to Touch: 30 Minutes</td> </tr> <tr> <td></td> <td>To Handle: 2 Hours</td> </tr> <tr> <td></td> <td>To Recoat: 1 Hour</td> </tr> <tr> <td>Shelf Life:</td> <td>18 months, unopened at 25 °C</td> </tr> <tr> <td>Reducer/Clean Up:</td> <td>Lacquer thinner YTF – K089</td> </tr> </table>	Color:	Above colors	Finish:	Flat	Volume Solid:	45% ± 2%	Specific Gravity:	1.40 KGs / ltr	Recommended DFT:	100 – 150 Microns	Spreading Rate@DFT:	4.50 m ² / ltr or 17 m ² / US gallon	Flash Point:	4 °C	Drying Schedule:		@ 25 °C/R.H.50	Dry to Touch: 30 Minutes		To Handle: 2 Hours		To Recoat: 1 Hour	Shelf Life:	18 months, unopened at 25 °C	Reducer/Clean Up:	Lacquer thinner YTF – K089	<table border="0"> <tr> <td>Lacquer Sanding Sealer</td> <td>1 Coat</td> <td>25 Microns DFT</td> </tr> <tr> <td>Industrial Lacquer Putty</td> <td>1 Coat</td> <td>150 Microns DFT</td> </tr> <tr> <td>Industrial Lacquer</td> <td>2 Coats</td> <td>25 Microns DFT per coat</td> </tr> </table> <p>Previously Painted Surfaces: Surfaces should be free from all foreign material. Old paint films must be brush blasted or scuff sanded prior to coating. Unknown old paint surface should be tested for lifting or peeling. If it does, clean to sound substrate and treat as new surface.</p> <p>*For further information on recommended products please refer to Sherwin Williams Saudi Arabia Painting & Coatings System Guide.</p> <p>**For further information on surface preparation methods and application procedures please refer to Sherwin Williams Saudi Arabia Surface Preparation bulletin.</p>	Lacquer Sanding Sealer	1 Coat	25 Microns DFT	Industrial Lacquer Putty	1 Coat	150 Microns DFT	Industrial Lacquer	2 Coats	25 Microns DFT per coat
Color:	Above colors																																			
Finish:	Flat																																			
Volume Solid:	45% ± 2%																																			
Specific Gravity:	1.40 KGs / ltr																																			
Recommended DFT:	100 – 150 Microns																																			
Spreading Rate@DFT:	4.50 m ² / ltr or 17 m ² / US gallon																																			
Flash Point:	4 °C																																			
Drying Schedule:																																				
@ 25 °C/R.H.50	Dry to Touch: 30 Minutes																																			
	To Handle: 2 Hours																																			
	To Recoat: 1 Hour																																			
Shelf Life:	18 months, unopened at 25 °C																																			
Reducer/Clean Up:	Lacquer thinner YTF – K089																																			
Lacquer Sanding Sealer	1 Coat	25 Microns DFT																																		
Industrial Lacquer Putty	1 Coat	150 Microns DFT																																		
Industrial Lacquer	2 Coats	25 Microns DFT per coat																																		
APPLICATION PROCEDURES	SPECIAL TIPS																																			
<p>Surface Preparation: Surface must be dry, clean and in sound condition. Remove oil, dust, dirt, millscale or other foreign substance to ensure good adhesion. Minimum surface preparation methods to be followed for (1) Iron and Steel – SSPC-SP2 or SP3 (2) Aluminum and Galvanizing – SSPC-SP1. Allow weathering of new galvanized steel for six months prior to coating. (3) Wood should be clean, smooth, dust free. Sand the surface with suitable grit sand paper and remove all the dust with a tack cloth or blast of clean air.</p> <p>Application Methods: Putty Knife</p>	<p>Any further specific technical information can be obtained from SWSA if you email ask@sherwinwilliams.ae</p> <th data-bbox="785 1626 1522 1662">SAFETY PRECAUTIONS</th> <p>Apply under well-ventilated conditions. Do not breathe or inhale mist. When spraying, wear air mask. Avoid skin contact. Spillage on skin should immediately be removed with suitable cleanser, soap and water. Eyes should be flushed with water and medical attention sought immediately.</p>	SAFETY PRECAUTIONS																																		